

Attacks and Defenses for Trusted Execution Environments

Jo Van Bulck

Seminar in Cybersecurity, KU Leuven – November 15 2024

🏠 DistriNet, KU Leuven, Belgium ✉ jo.vanbulck@cs.kuleuven.be 🐦 [@jovanbulck](https://twitter.com/jovanbulck) 🌐 vanbulck.net

The Big Picture: Protecting Private Data



Data in transit



Data in use



Data at rest

The Big Picture: Protecting Private Data



Data in transit

✓ SSL/TLS etc.



Data in use



Data at rest

✓ Full disk encryption

The Big Picture: Protecting Private Data



Data in transit

- ✓ SSL/TLS etc.




Data in use

- ? Homomorphic encryption?
- ? Trusted Execution?
= Confidential Computing
= Hardware Enclaves



Data at rest

- ✓ Full disk encryption



The Rise of Trusted Execution Environments

arm



AMD

IBM


 NVIDIA

- 2004: ARM TrustZone
- 2015: **Intel Software Guard Extensions (SGX)**
- 2016: AMD Secure Encrypted Virtualization (SEV)
- 2018: IBM Protected Execution Facility (PEF)
- 2020: AMD SEV with Secure Nested Paging (SEV-SNP)
- 2022: Intel Trust Domain Extensions (TDX)
- 2023: ARM Confidential Compute Architecture (CCA)
- 2024: NVIDIA Confidential Computing




TEEs are here to stay...

Goal: Reducing Attack Surface with Enclaves




Traditional **layered designs**: Large **trusted computing base**

Goal: Reducing Attack Surface with Enclaves




Intel SGX promise: Hardware-level **isolation and attestation**

Reality: Privileged Side-Channel Attacks



Game changer: Untrusted OS → new class of powerful **side channels!**

Reality: Privileged Side-Channel Attacks



▢ Xu et al. "Controlled-channel attacks: Deterministic side channels for untrusted operating systems", IEEE S&P 2015.

Game Changer: Privileged “Bottom-Up” Adversary Model




Game Changer: Privileged “Bottom-Up” Adversary Model



Abuse privileged **operating system powers**
→ **New and unexpected attack vectors**

Research Agenda: Understanding Privileged Attack Surface



1. **Which** novel privileged attacks exist?
 - Uncover previously **unknown attack avenues**
2. **How** well can they be exploited in practice?
 - Develop **new techniques** and practical attack frameworks
3. **What** can be leaked?
 - Leak **metadata** and **data**

Systematizing the SGX Attack Landscape



*Metadata vs.
direct data;
confidentiality
vs. integrity*

Attack	Properties	x86 Interface						Constraints			
		PTE	GDT	IRQ	MSR	CR0	PMC	SMT	REP	SAS	Granular
<i>μ-arch contention</i>	Cache priming [181, 92, 29, 225, 79]	●	○	●	●	○	●	●	●	○	64 B
	Branch prediction [156, 59, 105]	●	○	●	●	●	●	●	●	○	Inst
	DRAM row buffer conflicts [263]	○	○	○	●	●	○	○	●	○	1-8 KiB
	False dependencies [180]	○	○	○	●	○	○	●	●	○	4 B
	Interrupt latency [256, 95, 208]	●	○	●	●	○	○	○	●	○	Inst
	Port contention [7]	○	○	○	●	○	○	●	●	○	μ-op
<i>Control channel</i>	Page faults [277]	●	○	○	○	○	○	○	○	○	4 KiB
	Page table A/D [258, 263]	●	○	●	○	●	○	●	○	○	4 KiB
	Page table flushing [258]	●	○	●	○	○	○	●	○	○	32 KiB
	Interrupt counting [182]	●	○	●	○	○	○	○	○	○	Inst
	IA32 segmentation faults [91]	●	●	●	○	○	○	○	○	○	1 B-4 KiB
	Alignment faults [254]	○	○	●	○	●	○	○	○	○	1 B
<i>Transient</i>	Foreshadow L1D extraction [249]	●	○	●	○	○	○	●	○	○	–
	Data sampling [223, 216, 211]	●	○	●	○	○	○	●	●	○	–
	Spectre [39, 148]	●	○	●	○	○	○	●	●	●	–
	Load value injection [251]	●	○	●	○	○	○	●	●	●	–
<i>Interface</i>	Memory safety [254, 154, 24, 266]	●	○	●	○	○	○	○	●	●	–
	Undervolting [188, 137, 210]	●	○	●	●	○	○	●	●	●	–
	Off-chip memory address bus [152]	●	○	●	○	●	○	○	○	○	64 B

Systematizing the SGX Attack Landscape


Attack	Properties	x86 Interface						Constraints			
		PTE	GDT	IRQ	MSR	CR0	PMC	SMT	REP	SAS	Granular
μ -arch contention	Cache priming [181, 92, 29, 225, 79]	●	○	●	●	●	●	●	●	○	64 B
	Branch prediction [156, 59, 105]	●	○	●	●	●	●	●	●	○	Inst
	DRAM row buffer conflicts [263]	○	○	○	●	●	○	○	●	○	1-8 KiB
	False dependencies [180]	○	○	○	●	○	○	○	○	○	
	Interrupt latency [256, 95, 208]	●	○	●	●	○	○	○	○	○	
	Port contention [7]	○	○	○	●	○	○	○	○	○	
Control channel	Page faults [277]	●	○	○	○	○	○	○	○	○	Inst
	Page table A/D [258, 263]	●	○	●	○	○	○	○	○	○	1 B-4 KiB
	Page table flushing [258]	●	○	●	○	○	○	○	○	○	1 B
	Interrupt counting [182]	●	○	●	○	○	○	○	○	○	
	IA32 segmentation faults [91]	●	●	●	○	○	○	○	○	○	
	Alignment faults [254]	○	○	●	○	●	○	○	○	○	
Transient	Foreshadow L1D extraction [249]	●	○	●	○	○	○	●	○	○	–
	Data sampling [223, 216, 211]	●	○	●	○	○	○	●	●	○	–
	Spectre [39, 148]	●	○	●	○	○	○	●	●	●	–
	Load value injection [251]	●	○	●	○	○	○	●	●	●	–
Interface	Memory safety [254, 154, 24, 266]	●	○	●	○	○	○	○	●	●	–
	Undervolting [188, 137, 210]	●	○	●	●	○	○	●	●	●	–
	Off-chip memory address bus [152]	●	○	●	○	●	○	○	○	○	64 B




Possibly every privileged CPU feature can be abused!



Privileged side channels to spy on **enclave-CPU interaction**
metadata



Transient-execution for **direct data extraction** from CPU



Unexpected (physical) **CPU interface** manipulations

TEE Attack Research Leads the Way . . .



TEE Attack Research Leads the Way ...



- Privileged TEE attacker models **sets the bar!**
- **Idealized execution environment** for attack research
- **Generalizations:** e.g., Foreshadow-NG, branch prediction, address translation, etc.





1. Privileged Side-Channel Attacks

A note on SGX side-channel attacks (Intel)

Protection from Side-Channel Attacks

Intel® SGX does not provide explicit protection from side-channel attacks. It is the enclave developer's responsibility to address side-channel attack concerns.

In general, enclave operations that require an OCall, such as thread synchronization, I/O, etc., are exposed to the untrusted domain. If using an OCall would allow an attacker to gain insight into enclave secrets, then there would be a security concern. This scenario would be classified as a side-channel attack, and it would be up to the ISV to design the enclave in a way that prevents the leaking of side-channel information.

An attacker with access to the platform can see what pages are being executed or accessed. This side-channel vulnerability can be mitigated by aligning specific code and data blocks to exist entirely within a single page.

More important, the application enclave should use an appropriate crypto implementation that is side channel attack resistant inside the enclave if side-channel attacks are a concern.





KEEP CALM

IT IS

OUT OF SCOPE

Vulnerable patterns: Secret-dependent code/data accesses

```
1 void secret_vote(char candidate)
2 {
3     if (candidate == 'a')
4         vote_candidate_a();
5     else
6         vote_candidate_b();
7 }
```

```
1 int secret_lookup(int s)
2 {
3     if (s > 0 && s < ARRAY_LEN)
4         return array[s];
5     return -1;
6
7 }
```


Vulnerable patterns: Secret-dependent code/data accesses

```
1 void secret_vote(char candidate)
2 {
3     if (candidate == 'a')
4         vote_candidate_a();
5     else
6         vote_candidate_b();
7 }
```


```
1 int secret_lookup(int s)
2 {
3     if (s > 0 && s < ARRAY_LEN)
4         return array[s];
5     return -1;
6
7 }
```

What are new ways for privileged adversaries to create an “oracle” for enclave code+data memory accesses?

Overview: Spying on enclave memory accesses



Overview: Spying on enclave memory accesses






1. Privileged Side-Channel Attacks


Idea #1: Monitoring Address Translation?

The virtual memory abstraction




Costan et al. "Intel SGX explained", IACR 2016.

Intel SGX: Page faults as a side channel




SGX machinery protects against direct address remapping attacks

Intel SGX: Page faults as a side channel



... but untrusted address translation may **fault(!)**

Intel SGX: Page faults as a side channel



□ Xu et al.: "Controlled-channel attacks: Deterministic side channels for untrusted operating systems", Oakland 2015.


⇒ Page fault traces leak **private control data/flow**

Page table-based attacks in practice

Original




Recovered



Original



Recovered



□ Xu et al.: "Controlled-channel attacks: Deterministic side channels for untrusted operating systems", Oakland 2015.


⇒ **Low-noise, single-run** exploitation of legacy applications

Page table-based attacks in practice

Original




Recovered



Original



Recovered



□ Xu et al.: "Controlled-channel attacks: Deterministic side channels for untrusted operating systems", Oakland 2015.


... but **many faults** and a coarse-grained **4 KiB granularity**



1. Privileged Side-Channel Attacks

Idea #2: Monitoring without Page Faults?


Naive solutions: Hiding enclave page faults



Shih et al. "T-SGX: Eradicating controlled-channel attacks against enclave programs", NDSS 2017.

Shinde et al. "Preventing page faults from telling your secrets", AsiaCCS 2016.

Naive solutions: Hiding enclave page faults



... But stealthy attacker can learn page visits without triggering faults!

Documented side-effects of address translation

4.8 ACCESSED AND DIRTY FLAGS

For any paging-structure entry that is used during linear-address translation, bit 5 is the **accessed** flag.² For paging-structure entries that map a page (as opposed to referencing another paging structure), bit 6 is the **dirty** flag. These flags are provided for use by memory-management software to manage the transfer of pages and paging structures into and out of physical memory.

Whenever the processor uses a paging-structure entry as part of linear-address translation, it sets the accessed flag in that entry (if it is not already set).


Whenever there is a write to a linear address, the processor sets the dirty flag (if it is not already set) in the paging-structure entry that identifies the final physical address for the linear address (either a PTE or a paging-structure entry in which the PS flag is 1).

Telling your secrets without page faults

1. Attack vector: PTE status flags:

- A(ccessed) bit
- D(irty) bit

~> Also updated in enclave mode!



Telling your secrets without page faults

1. Attack vector: PTE status flags:


- A(ccessed) bit
- D(irty) bit

→ Also updated in enclave mode!

2. **Attack vector:** Unprotected **page table** **memory:**

- Cached as regular data
- Accessed during address translation

→ Flush+Reload cache timing attack!



Attacking Libcrypt EdDSA (simplified)

```
1  if (mpi_is_secure (scalar)) {  
2      /* If SCALAR is in secure memory we assume that it is the  
3         secret key we use constant time operation. */  
4      point_init (&tmppnt);  
5  
6      for (j=nbits-1; j >= 0; j--) {  
7          _gcry_mpi_ec_dup_point (result, result, ctx);  
8          _gcry_mpi_ec_add_points (&tmppnt, result, point, ctx);  
9          point_swap_cond (result, &tmppnt, mpi_test_bit (scalar, j), ctx);  
10     }  
11     point_free (&tmppnt);  
12 } else {  
13     for (j=nbits-1; j >= 0; j--) {  
14         _gcry_mpi_ec_dup_point (result, result, ctx);  
15         if (mpi_test_bit (scalar, j))  
16             _gcry_mpi_ec_add_points (result, result, point, ctx);  
17     }  
18 }
```

Memory layout

...	
gcry_free	0x0F000
...	
mpi_add	0xC0000
mpi_test_bit	0xC1000
...	
mpi_ec_add_p	0xC9000
mpi_ec_mul_p	0xCA000
...	

**22 Code pages
per iteration**

Attacking Libcrypt EdDSA (simplified)

```
1  if (mpi_is_secure (scalar)) {
2      /* If SCALAR is in secure memory we assume that it is the
3       secret key we use constant time operation. */
4      point_init (&tmppnt);
5
6      for (j=nbits-1; j >= 0; j--) {
7          _gcry_mpi_ec_dup_point (result, result, ctx);
8          _gcry_mpi_ec_add_points (&tmppnt, result, point, ctx);
9          point_swap_cond (result, &tmppnt, mpi_test_bit (scalar, j), ctx);
10     }
11     point_free (&tmppnt);
12 } else {
13     for (j=nbits-1; j >= 0; j--) {
14         _gcry_mpi_ec_dup_point (result, result, ctx);
15         if (mpi_test_bit (scalar, j))
16             _gcry_mpi_ec_add_points (result, result, point, ctx);
17     }
18 }
```

**Monitor
trigger page**



Memory layout

...	
gcry_free	0x0F000
...	
mpi_add	0xC0000
mpi_test_bit	0xC1000
...	
mpi_ec_add_p	0xC9000
mpi_ec_mul_p	0xCA000
...	

Attacking Libgcrypt EdDSA (simplified)

```
1  if (mpi_is_secure (scalar)) {
2      /* If SCALAR is in secure memory we assume that it is the
3       secret key we use constant time operation. */
4      point_init (&tmppnt);
5
6      for (j=nbits-1; j >= 0; j--) {
7          _gcry_mpi_ec_dup_point (result, result, ctx);
8          _gcry_mpi_ec_add_points (&tmppnt, result, point, ctx);
9          point_swap_cond (result, &tmppnt, mpi_test_bit (scalar, j), ctx);
10     }
11     point_free (&tmppnt);
12 } else {
13     for (j=nbits-1; j >= 0; j--) {
14         _gcry_mpi_ec_dup_point (result, result, ctx);
15         if (mpi_test_bit (scalar, j))
16             _gcry_mpi_ec_add_points (result, result, point, ctx);
17     }
18 }
```

Memory layout

...	
gcry_free	0x0F000
...	
mpi_add	0xC0000
mpi_test_bit	0xC1000
...	
mpi_ec_add_p	0xC9000
mpi_ec_mul_p	0xCA000
...	



INTERRUPT

Attacking Libgcrypt EdDSA (simplified)

```
1 if (mpi_is_secure (scalar)) {  
2     /* If SCALAR is in secure memory we assume that it is the  
3        secret key we use constant time operation. */  
4     point_init (&tmppnt);  
5  
6     for (j=nbits-1; j >= 0; j--) {  
7         _gcry_mpi_ec_dup_point (result, result, ctx);  
8         _gcry_mpi_ec_add_points (&tmppnt, result, point, ctx);  
9         point_swap_cond (result, &tmppnt, mpi_test_bit (scalar, j), ctx);  
10    }  
11    point_free (&tmppnt);  
12 } else {  
13     for (j=nbits-1; j >= 0; j--) {  
14         _gcry_mpi_ec_dup_point (result, result, ctx);  
15         if (mpi_test_bit (scalar, j))  
16             _gcry_mpi_ec_add_points (result, result, point, ctx);  
17     }  
18 }
```

Record page set
0011

ACCESSED ?



ACCESSED ?

Memory layout

...	
gcry_free	0x0F000
...	
mpi_add	0xC0000
mpi_test_bit	0xC1000
...	
mpi_ec_add_p	0xC9000
mpi_ec_mul_p	0xCA000
...	

Attacking Libgcrypt EdDSA (simplified)

```
1  if (mpi_is_secure (scalar)) {
2      /* If SCALAR is in secure memory we assume that it is the
3       secret key we use constant time operation. */
4      point_init (&tmppnt);
5
6      for (j=nbits-1; j >= 0; j--) {
7          _gcry_mpi_ec_dup_point (result, result, ctx);
8          _gcry_mpi_ec_add_points (&tmppnt, result, point, ctx);
9          point_swap_cond (result, &tmppnt, mpi_test_bit (scalar, j), ctx);
10     }
11     point_free (&tmppnt);
12 } else {
13     for (j=nbits-1; j >= 0; j--) {
14         _gcry_mpi_ec_dup_point (result, result, ctx);
15         if (mpi_test_bit (scalar, j))
16             _gcry_mpi_ec_add_points (result, result, point, ctx);
17     }
18 }
```

Full 512-bit key recovery, single run

Memory layout

...	
gcry_free	0x0F000
...	
mpi_add	0xC0000
mpi_test_bit	0xC1000
...	
mpi_ec_add_p	0xC9000
mpi_ec_mul_p	0xCA000
...	



RESUME

Side-channel analysis: From metadata patterns to secrets

Handwritten notes and annotations on a slide showing memory addresses and assembly instructions.

Handwritten notes:

- Top left: **I** (in a red triangle), **more pages accessed...**
- Right side: **~p. 27**
- Bottom left: **MONITOR** (with an arrow pointing to the address 0x7ffff7ba0000)
- Bottom center: **IRQ** (with an arrow pointing to the instruction <gcry_mpi_ec_mul_point+1111>)
- Right side: **GPG ERR** (in a red box, pointing to <gpg_err_set_errno>)
- Bottom right: **ONE <? ZERO** (in a blue box, pointing to <gcry_mpi_test_bit>)
- Far right: **7B87#** and **7BA0**


Table of memory addresses and instructions:

Address	Offset	Instruction
0x7ffff7b9e000	28	<gcry_mpi_free_limb_space>
0x7ffff7b03000	7	<gcry_free>
0x7ffff7aff000	1	<_errno_location@plt>
0x7ffff774e000	3	<_GI__errno_location>
0x7ffff7b03000	6	<gcry_free+19>
0x7ffff7b08000	17	<gcry_private_free>
0x7ffff7aff000	1	<free@plt>
0x7ffff77b1000	20	<_GI__libc_free>
0x7ffff77ad000	78	<int_free>
0x7ffff77b1000	6	<_GI__libc_free+76>
0x7ffff7b03000	8	<gcry_free+77>
0x7ffff7aff000	1	<gpg_err_set_errno@plt>
0x7ffff7524000	1	<gpg_err_set_errno>
0x7ffff751b000	4	<gpg_err_set_errno>
0x7ffff774e000	3	<_GI__errno_location>
0x7ffff751b000	3	<gpg_err_set_errno+8>
0x7ffff7b98000	26	<gcry_mpi_tdiv_qr+500>
0x7ffff7ba0000	3	<gcry_mpi_ec_mul_point+1081>
0x7ffff7b97000	11	<gcry_mpi_test_bit>
0x7ffff7ba0000	6	<gcry_mpi_ec_mul_point+1092>
0x7ffff7b9e000	176	<point_set>
0x7ffff7ba0000	2	<gcry_mpi_ec_mul_point+1111>

Scientific Understanding Driven by Attacker-Defender Race . . .



Scientific Understanding Driven by Attacker-Defender Race . . .





1. Privileged Side-Channel Attacks

Idea #3: Spatial vs. Temporal Resolution?

Intel's note on side-channel attacks (revisited)

Protection from Side-Channel Attacks

Intel® SGX does not provide explicit protection from side-channel attacks. It is the enclave developer's responsibility to address side-channel attack concerns.

In general, enclave operations that require an OCall, such as thread synchronization, I/O, etc., are exposed to the untrusted domain. If using an OCall would allow an attacker to gain insight into enclave secrets, then there would be a security concern. This scenario would be classified as a side-channel attack, and it would be up to the ISV to design the enclave in a way that prevents the leaking of side-channel information.

An attacker with access to the platform can see what pages are being executed or accessed. This side-channel vulnerability can be mitigated by aligning specific code and data blocks to exist entirely within a single page.

More important, the application enclave should use an appropriate crypto implementation that is side channel attack resistant inside the enclave if side-channel attacks are a concern.



Temporal resolution limitations for the page fault oracle

```
1 size_t strlen (char *str)
2 {
3     char *s;
4
5     for (s = str; *s; ++s);
6     return (s - str);
7 }
```

```
1     mov    %rdi,%rax
2 1:  cmpb   $0x0,(%rax)
3     je     2f
4     inc    %rax
5     jmp    1b
6 2:  sub    %rdi,%rax
7     retq
```


⇒ tight loop: 4 instructions, single memory operand, single code + data page

Counting strlen loop iterations?



Note: Page-fault attacks cannot make progress for 1 code + data page

Temporal resolution limitations for the page fault oracle




Counting strlen loop iterations?



Progress requires **both pages present** (non-faulting) ↔ page fault oracle


Building the `strlen()` side-channel oracle with execution timing?



Building the `strlen()` side-channel oracle with execution timing?



Too noisy: modern x86 processors are lightning fast...



Challenge: Side-channel Sampling Rate



**Slow
shutter speed**




**Medium
shutter speed**




**Fast
shutter speed**

SGX-Step: Executing Enclaves one Instruction at a Time



SGX-Step: Executing Enclaves one Instruction at a Time



SGX-Step demo: Building a memcmp() Password Oracle

```
[idt.c] DTR.base=0xffffffff0000000000/size=4095 (256 entries)
[idt.c] established user space IDT mapping at 0x7f7ff8e9a000
[idt.c] installed asm IRQ handler at 10:0x56312d19b000
[idt.c] IDT[ 45] @0x7f7ff8e9a2d0 = 0x56312d19b000 (seg sel 0x10); p=1; dpl=3; type=14; ist=0
[file.c] reading buffer from '/dev/cpu/1/msr' (size=8)
[apic.c] established local memory mapping for APIC_BASE=0xf0000000 at 0x7f7ff8e99000
[apic.c] APIC_ID=20000000; LVTT=400ec; TDCR=0
[apic.c] APIC timer one-shot mode with division 2 (lvtt=2d/tdcr=0)
```

```
-----
[main.c] recovering password length
-----
```

```
[attacker] steps=15; guess='*****'
[attacker] found pwd len = 6
```

```
-----
[main.c] recovering password bytes
-----
```

```
[attacker] steps=35; guess='SECRET' --> SUCCESS
```


```
[apic.c] Restored APIC_LVTT=400ec/TDCR=0)
[file.c] writing buffer to '/dev/cpu/1/msr' (size=8)
[main.c] all done; counted 2260/2183 IRQs (AEP/IDT)
jo@breuer:~/sgx-step-demo$ █
```

SGX-Step: Enabling a New Line of High-Resolution Attacks

Yr	Venue	Paper	Step	Use Case	Drv
'15	S&P	Ctrl channel	~ Page	Probe (page fault)	✓
'16	ESORICS	AsyncShock	~ Page	Exploit (mem safety)	–
'17	CHES	CacheZoom	✗ >1	Probe (L1 cache)	✓
'17	ATC	Hahnel et al.	✗ 0 - >1	Probe (L1 cache)	✓
'17	USENIX	BranchShadow	✗ 5 - 50	Probe (BPU)	✗
'17	USENIX	Stealthy PTE	~ Page	Probe (page table)	✓
'17	USENIX	DarkROP	~ Page	Exploit (mem safety)	✓
'17	SysTEX	SGX-Step	✓ 0 - 1	Framework	✓
'18	ESSoS	Off-limits	✓ 0 - 1	Probe (segmentation)	✓
'18	AsiaCCS	Single-trace RSA	~ Page	Probe (page fault)	✓
'18	USENIX	Foreshadow	✓ 0 - 1	Probe (transient exec)	✓
'18	EuroS&P	SgxPectre	~ Page	Exploit (transient)	✓
'18	CHES	CacheQuote	✗ >1	Probe (L1 cache)	✓
'18	ICCD	SGXlinger	✗ >1	Probe (IRQ latency)	✗
'18	CCS	Nemesis	✓ 1	Probe (IRQ latency)	✓
'19	USENIX	Spoiler	✓ 1	Probe (IRQ latency)	✓
'19	CCS	ZombieLoad	✓ 0 - 1	Probe (transient exec)	✓
'19	CCS	Fallout	–	Probe (transient exec)	✓
'19	CCS	Tale of 2 worlds	✓ 1	Exploit (mem safety)	✓
'19	ISCA	MicroScope	~ 0 - Page	Framework	✗
'20	CHES	Bluthunder	✓ 1	Probe (BPU)	✓
'20	USENIX	Big troubles	~ Page	Probe (page fault)	✓
'20	S&P	Plundervolt	–	Exploit (undervolt)	✓
'20	CHES	Viral primitive	✓ 1	Probe (IRQ count)	✓
'20	USENIX	CopyCat	✓ 1	Probe (IRQ count)	✓
'20	S&P	LVI	✓ 1	Exploit (transient)	✓

Yr	Venue	Paper	Step	Use Case	Drv
'20	CHES	A to Z	~ Page	Probe (page fault)	✓
'20	CCS	Déjà Vu NSS	~ Page	Probe (page fault)	✓
'20	MICRO	PTHammer	–	Probe (page walk)	✓
'21	USENIX	Frontal	✓ 1	Probe (IRQ latency)	✓
'21	S&P	CrossTalk	✓ 1	Probe (transient exec)	✓
'21	CHES	Online template	✓ 1	Probe (IRQ count)	✓
'21	NDSS	SpeechMiner	–	Framework	✓
'21	S&P	Platypus	✓ 0 - 1	Probe (voltage)	✓
'21	DIMVA	Aion	✓ 1	Probe (cache)	✓
'21	CCS	SmashEx	✓ 1	Exploit (mem safety)	✓
'21	CCS	Util::Lookup	✓ 1	Probe (L3 cache)	✓
'22	USENIX	Rapid prototyping	✓ 1	Framework	✓
'22	CT-RSA	Kalyana expansion	✓ 1	Probe (L3 cache)	✓
'22	SEED	Enclyzer	–	Framework	✓
'22	NordSec	Self-monitoring	~ Page	Defense (detect)	✓
'22	AutoSec	Robotic vehicles	✓ 1 - >1	Exploit (timestamp)	✓
'22	ACSAC	MoLE	✓ 1	Defense (randomize)	✓
'22	USENIX	AEPIC	✓ 1	Probe (I/O device)	✓
'22	arXiv	Confidential code	✓ 1	Probe (IRQ latency)	✓
'23	ComSec	FaultMorse	~ Page	Probe (page fault)	✓
'23	CHES	HQC timing	✓ 1	Probe (L3 cache)	✓
'23	ISCA	Belong to us	✓ 1	Probe (BPU)	✓
'23	USENIX	BunnyHop	✓ 1	Probe (BPU)	✓
'23	USENIX	DownFall	✓ 0 - 1	Probe (transient exec)	✓
'23	USENIX	AEX-Notify	✓ 1	Defense (prefetch)	✓

A Versatile Open-Source Attack Toolkit







1. Privileged Side-Channel Attacks

Idea #4: Interrupt Hardening?

Root-causing SGX-Step: Aiming the timer interrupt



Root-causing SGX-Step: Microcode assists to the rescue!

PTE A-bit	Mean (cycles)	Stddev (cycles)
A=1	27	30
A=0	666	55



3. Assisted PT walk



1. Clear PTE A-bit



2. TLB flush




page walk (\$RIP)

exec


Arm timer

ERESUME

NOP₁






AEX-Notify solution overview



AEX-Notify solution overview

We implemented a fast, constant-time decoder (CTD)



CHAPTER 8

ASYNCHRONOUS ENCLAVE EXIT NOTIFY AND THE EDECCSSA USER LEAF FUNCTION

8.1 INTRODUCTION

Asynchronous Enclave Exit Notify (AEX-Notify) is an extension to Intel® SGX that allows Intel SGX enclaves to be notified after an asynchronous enclave exit (AEX) has occurred. EDECCSSA is a new Intel SGX user leaf function (ENCLU[EDECCSSA]) that can facilitate AEX notification handling, as well as software exception handling. This chapter provides information about changes to the Intel SGX architecture that support AEX-Notify and ENCLU[EDECCSSA].

The following list summarizes the details are provided in Section 8.3)

- SECS.ATTRIBUTES.AEXNOTIFY
- TCS.FLAGS.AEXNOTIFY: This e
- SSA.GPRSGX.AEXNOTIFY: Enclave-writable byte that allows enclave software to dynamically enable/disable AEX notifications.

An AEX notification is delivered by ENCLU[ERESUME] when the following conditions are met:



SGX-Step led to new x86 processor instructions!

→ shipped in millions of devices ≥ 4th Gen Xeon CPU

Intel AEX Notify Support Prepped For Linux To Help Enhance SGX Enclave Security

Written by [Michael Larabel](#) in [Intel](#) on 6 November 2022 at 06:01 AM EST. [5 Comments](#)



Future Intel CPUs and some existing processors via a microcode update will support a new feature called the Asynchronous EXit (AEX) notification mechanism to help with Software Guard Extensions (SGX) enclave security. Patches for the Linux kernel are pending for implementing this Intel AEX Notify support with capable processors.

Intel's Asynchronous EXit (AEX) notification mechanism lets SGX enclaves run a handler after an AEX event. Those handlers can be used for things like mitigating SGX-Step as an attack framework for precise enclave execution control.



Code 1 in Intel/linux-sgx X

Filter ...

▼ sdk/trts/linux/trts_mitigation.S

```
48  * Description:
49  *   The file provides mitigations for SGX-Step
50  */
71  * Function:
   constant_time_apply_sgxstep_mitigation_and_continue_execution
72  *   Mitigate SGX-Step and return to the point at which the
   most recent
73  *   interrupt/exception occurred.
```



SGX-Step led to changes in major OSs and enclave SDKs




2. Transient-Execution Attacks

Revisited: Intel's note on side-channel attacks (2017)


"In general, these research papers do not demonstrate anything new or unexpected about the Intel SGX architecture. Preventing side channel attacks is a matter for the enclave developer. Intel makes this clear in the security objectives for Intel SGX."

<https://www.intel.com/content/www/us/en/developer/articles/technical/intel-sgx-and-side-channels.html>

Recap: Privileged side-channel attacks



Recap: Transient-execution attacks




A close-up of Morpheus from the movie The Matrix, wearing his signature black sunglasses. The reflection in the lenses shows three figures in a combat stance. The background is a blurred, dimly lit interior.


WHAT IF I TOLD YOU

YOU CAN CHANGE RULES MID-GAME


Abusing out-of-order and speculative execution



Abusing out-of-order and speculative execution



Abusing out-of-order and speculative execution




Transient-execution attacks: Welcome to the world of fun!



The transient-execution zoo

<https://transient.fail>



Rumors: Meltdown immunity for SGX enclaves?

Meltdown melted down everything, except for one thing

“[enclaves] remain [protected and completely secure](#)”

— *International Business Times*, February 2018

*ANJUNA'S SECURE-RUNTIME CAN PROTECT CRITICAL APPLICATIONS
AGAINST THE MELTDOWN ATTACK USING ENCLAVES*

“[enclave memory accesses] redirected to an [abort page](#), which has no value”

— *Anjuna Security, Inc.*, March 2018

~~Rumors: Meltdown immunity for SGX enclaves?~~



LILY HAY-NEWMAN SECURITY 08.14.18 01:00 PM


SPECTRE-LIKE FLAW UNDERMINES INTEL PROCESSORS' MOST SECURE ELEMENT

I'M SURE THIS WON'T BE THE LAST SUCH PROBLEM —


Intel's SGX blown wide open by, you guessed it, a speculative execution attack

Speculative execution attacks truly are the gift that keeps on giving.






Building Foreshadow: Evade SGX abort page semantics




SGX checks prohibit unauthorized access

Building Foreshadow: Evade SGX abort page semantics




SGX checks prohibit unauthorized access

Building Foreshadow: Evade SGX abort page semantics




...but attackers can **unmap** enclave pages!

The microarchitecture behind Foreshadow




L1 cache design: Virtually-indexed, physically-tagged

The microarchitecture behind Foreshadow




Page fault: Early-out address translation

The microarchitecture behind Foreshadow




L1-Terminal Fault: Match *unmapped physical address* (!)

The microarchitecture behind Foreshadow



Foreshadow-SGX: Bypass enclave isolation

The microarchitecture behind Foreshadow



Foreshadow-NG: Bypass virtual machine isolation



a

>


S



Enclave Memory


[illegible][illegible][illegible]

Foreshadow: Extracting the keys to the Intel SGX kingdom



Intel == trusted 3th party (shared **CPU master secret**)

Foreshadow: Extracting the keys to the Intel SGX kingdom




Extract long-term platform **attestation key** → forge Intel signatures

Mitigating Foreshadow: Flush CPU microarchitecture




Mitigating Foreshadow: Flush CPU microarchitecture



10BH	267	IA32_FLUSH_CMD	Flush Command (WO) Gives software a way to invalidate structures with finer granularity than other architectural methods.	If any one of the enumeration conditions for defined bit field positions holds.
		0	L1D_FLUSH: Writeback and invalidate the L1 data cache.	If CPUID.(EAX=07H, ECX=0):EDX[28]=1
		63:1	Reserved	

MDS variants: Flushing additional microarchitectural buffers



MDS variants: Address dependencies

	Page Number			Page Offset		
Meltdown	51	Physical	12	11	0	
	47	Virtual	12			
Foreshadow	51	Physical	12	11	0	
	47	Virtual	12			
Fallout	51	Physical	12	11	0	
	47	Virtual	12			
ZombieLoad/ RIDL	51	Physical	12	11	6	5 0
	47	Virtual	12			



Take-away: Addressability $\neq$ (transient) accessibility

Meltdown take-away

Faulting (or assisted) loads transiently forward **unrelated data** from various microarchitectural buffers



Idea: Can we turn Foreshadow around?



Outside view

- Meltdown: out-of-reach
- Foreshadow: cache emptied



Intra-enclave view

- Access enclave + outside memory

Idea: Can we turn Foreshadow around?



Outside view


- Meltdown: out-of-reach
- Foreshadow: cache emptied




Intra-enclave view

- Access enclave + outside memory
→ Abuse **in-enclave code gadgets!**


Reviving Foreshadow with Load Value Injection (LVI)




Reviving Foreshadow with Load Value Injection (LVI)




LVI: The basic idea




LVI: The basic idea




LVI: The basic idea




LVI: The basic idea




LVI: The basic idea



LVI: The basic idea



LVI: The basic idea



FOOD POISONING



Overdue products



Medicine



Dizziness



Intestinal colic




Diarrhea




Headache



Taxonomy of LVI variants: Many buffers, many faults...




LVI-based transient control-flow hijacking




1. Victim fills μ -arch buffer with attacker-controlled data

LVI-based transient control-flow hijacking




1. Victim fills μ -arch buffer with attacker-controlled data
2. Victim executes indirect branch (JMP/CALL/RET)

LVI-based transient control-flow hijacking



1. Victim **fills μ -arch buffer** with attacker-controlled data
2. Victim executes indirect branch (JMP/CALL/RET)
3. Faulting load $\rightarrow$ inject incorrect attacker values(!)

LVI-based transient control-flow hijacking



1. Victim fills μ -arch buffer with attacker-controlled data
2. Victim executes indirect branch (JMP/CALL/RET)
3. Faulting load → inject incorrect attacker values(!)
4. Redirect **transient control flow**

```
E/asm.S main.c
28 .global ecall_lvi_sb_rop
29 # %rdi store_pt
30 # %rsi oracle_pt
31 ecall_lvi_sb_rop:
32 mov %rsp, rsp_backup(%rip)
33 lea page_b(%rip), %rsp
34 add $OFFSET, %rsp
35
36 /* transient delay */
37 clflush dummy(%rip)
38 mov dummy(%rip), %rax
39
40 /* STORE TO USER ADRS */
41 movq $'R', (%rdi)
42 lea ret_gadget(%rip), %rax
43 movq %rax, 8(%rdi)
44
45 /* HIJACK TRUSTED LOAD FROM ENCLAVE STACK */
46 /* should go to do_real_ret; will transiently go to ret_gadget if we fault on the stack loads */
47 pop %rax
48 #if LFENCE
49 notq (%rsp)
50 notq (%rsp)
51 lfence
52 ret
53 #else
54 ret
55 #endif
56
57 1: jmp 1b
58 mfence
59
60 do_real_ret:
61 mov rsp_backup(%rip), %rsp
62 ret
63
```

Mitigating LVI: Fencing vulnerable load instructions



Mitigating LVI: Fencing vulnerable load instructions




LFENCE—Load Fence

Opcode	Instruction	Op/ En	64-Bit Mode	Compat/ Leg Mode	Description
NP OF AE E8	LFENCE	Z0	Valid	Valid	Serializes load operations.



Mitigation idea: Fencing vulnerable load instructions



Mitigating LVI: Compiler and assembler support



`-mlfence-after-load`

GNU Assembler Adds New Options For Mitigating Load Value Injection Attack

Written by [Michael Larabel](#) in [GNU](#) on 11 March 2020 at 02:55 PM EDT. [14 Comments](#)



`-mlvi-hardening`

LLVM Lands **Performance-Hitting Mitigation** For Intel LVI Vulnerability


Written by [Michael Larabel](#) in [Software](#) on 3 April 2020. **Page 1 of 3.** [20 Comments](#)



`-Qspectre-load`


More Spectre Mitigations in **MSVC**

March 13th, 2020





23 fences

October 2019—“surgical precision”



23 fences

October 2019—"surgical precision"



49,315 fences

March 2020—"big hammer"





3. Privileged CPU Interface Attacks

Security perimeter for CPU-based isolation?



Security perimeter for CPU-based isolation?



SGX (wants to) only trust the **CPU package**


↔ CPU interfaces with the *physical world(!)*

- (Encrypted) memory bus
- **Power supply**
- I/O devices

With great power comes great leakage . . .



With great power comes great leakage . . .



□ Lipp et al. "PLATYPUS: Software-based Power Side-Channel Attacks on x86", S&P 21.



Requirements: **Software-only** attacker → *Metadata + direct data leakage(!)*

TEMPERATURES

I5 9300H

UNDervolt OFF

UNDervolt ON

95°C

203°F



83°C

179°F

Utilization
- %
Processor Cache Frequency
3.69 GHz
Current Limit Throttling
No

Memory
3074
Active
4
Motherboard VR Thermal...

Package TDP
34 W

5 Minutes



Warning

Altering clock frequency or voltage may:

- damage or reduce the useful life of the processor and other system components
- may reduce system stability and performance.



Product warranties may not apply if the processor is operated beyond its specifications. Check with the manufacturers of system and components for additional details.

I agree


I agree, don't show again

Cancel

How a little bit of undervolting can cause a lot of problems . . .



How a little bit of undervolting can cause a lot of problems ...





Conclusions and Outlook



Takeaways

- ⇒ **Trusted execution** environments (Intel SGX) $\neq$ perfect!
- ⇒ Privileged adversaries: Subtle **side channels** can go a long way...
- ⇒ Scientific understanding driven by **attacker-defender race**



Takeaways

- ⇒ **Trusted execution** environments (Intel SGX) $\neq$ perfect!
- ⇒ Privileged adversaries: Subtle **side channels** can go a long way...
- ⇒ Scientific understanding driven by **attacker-defender race**



Thank you! Questions?