

~~Secure~~ Trusted Software and Hacking

Jo Van Bulck

Guest Lecture – May 21, 2025

🏠 DistriNet, KU Leuven, Belgium ✉ jo.vanbulck@cs.kuleuven.be 🐦 @jovanbulck 🌐 vanbulck.net

The Big Picture: Protecting Private Data



Data in transit



Data in use



Data at rest

The Big Picture: Protecting Private Data



Data in transit

✓ SSL/TLS etc.



Data in use



Data at rest

✓ Full disk
encryption

The Big Picture: Protecting Private Data



Data in transit

- ✓ SSL/TLS etc.




Data in use

- ? Homomorphic encryption?
- ? Trusted Execution?
= Confidential Computing
= Hardware Enclaves



Data at rest

- ✓ Full disk encryption



The Rise of Trusted Execution Environments

arm



AMD

IBM


 NVIDIA

- 2004: ARM TrustZone
- 2015: **Intel Software Guard Extensions (SGX)**
- 2016: AMD Secure Encrypted Virtualization (SEV)
- 2018: IBM Protected Execution Facility (PEF)
- 2020: AMD SEV with Secure Nested Paging (SEV-SNP)
- 2022: Intel Trust Domain Extensions (TDX)
- 2023: ARM Confidential Compute Architecture (CCA)
- 2024: NVIDIA Confidential Computing




TEEs are here to stay...

Goal: Reducing Attack Surface with Enclaves




Traditional **layered** designs: Large **trusted** computing base

Goal: Reducing Attack Surface with Enclaves




Intel SGX promise: Hardware-level **isolation and attestation**

Reality: Privileged Side-Channel Attacks



Game changer: Untrusted OS → new class of powerful **side channels!**

Reality: Privileged Side-Channel Attacks



▢ Xu et al. "Controlled-channel attacks: Deterministic side channels for untrusted operating systems", IEEE S&P 2015.

Game Changer: Privileged “Bottom-Up” Adversary Model




Game Changer: Privileged “Bottom-Up” Adversary Model



Abuse privileged **operating system powers**
→ **New and unexpected attack vectors**

Research Agenda: Understanding Privileged Attack Surface



1. **Which** novel privileged attacks exist?
 - Uncover previously **unknown attack avenues**
2. **How** well can they be exploited in practice?
 - Develop **new techniques** and practical attack frameworks
3. **What** can be leaked?
 - Leak **metadata** and **data**

TEE Attack Research Leads the Way ...



TEE Attack Research Leads the Way ...



- Privileged TEE attacker models **sets the bar!**
- **Idealized execution environment** for attack research
- **Generalizations:** e.g., Foreshadow-NG, branch prediction, address translation, etc.





1. Privileged Side-Channel Attacks

A note on SGX side-channel attacks (Intel)

Protection from Side-Channel Attacks

Intel® SGX does not provide explicit protection from side-channel attacks. It is the enclave developer's responsibility to address side-channel attack concerns.

In general, enclave operations that require an OCall, such as thread synchronization, I/O, etc., are exposed to the untrusted domain. If using an OCall would allow an attacker to gain insight into enclave secrets, then there would be a security concern. This scenario would be classified as a side-channel attack, and it would be up to the ISV to design the enclave in a way that prevents the leaking of side-channel information.

An attacker with access to the platform can see what pages are being executed or accessed. This side-channel vulnerability can be mitigated by aligning specific code and data blocks to exist entirely within a single page.

More important, the application enclave should use an appropriate crypto implementation that is side channel attack resistant inside the enclave if side-channel attacks are a concern.





KEEP CALM
IT IS
OUT OF SCOPE

Vulnerable patterns: Secret-dependent code/data accesses

```
1 void secret_vote(char candidate)
2 {
3     if (candidate == 'a')
4         vote_candidate_a();
5     else
6         vote_candidate_b();
7 }
```

```
1 int secret_lookup(int s)
2 {
3     if (s > 0 && s < ARRAY_LEN)
4         return array[s];
5     return -1;
6
7 }
```


Vulnerable patterns: Secret-dependent code/data accesses

```
1 void secret_vote(char candidate)
2 {
3     if (candidate == 'a')
4         vote_candidate_a();
5     else
6         vote_candidate_b();
7 }
```


```
1 int secret_lookup(int s)
2 {
3     if (s > 0 && s < ARRAY_LEN)
4         return array[s];
5     return -1;
6
7 }
```

What are new ways for privileged adversaries to create an “oracle” for enclave code+data memory accesses?

Overview: Spying on enclave memory accesses



Overview: Spying on enclave memory accesses






1. Privileged Side-Channel Attacks


Idea #1: Monitoring Address Translation?

The virtual memory abstraction




Costan et al. "Intel SGX explained", IACR 2016.

Intel SGX: Page faults as a side channel




SGX machinery protects against direct address remapping attacks

Intel SGX: Page faults as a side channel



... but untrusted address translation may **fault(!)**

Intel SGX: Page faults as a side channel



□ Xu et al.: "Controlled-channel attacks: Deterministic side channels for untrusted operating systems", Oakland 2015.

⇒ Page fault traces leak **private control data/flow**

Page table-based attacks in practice

Original




Recovered



Original



Recovered



□ Xu et al.: "Controlled-channel attacks: Deterministic side channels for untrusted operating systems", Oakland 2015.

⇒ **Low-noise, single-run** exploitation of legacy applications

Page table-based attacks in practice

Original




Recovered



Original



Recovered



□ Xu et al.: "Controlled-channel attacks: Deterministic side channels for untrusted operating systems", Oakland 2015.


... but **many faults** and a coarse-grained **4 KiB granularity**



1. Privileged Side-Channel Attacks

Idea #2: Monitoring without Page Faults?


Naive solutions: Hiding enclave page faults



Shih et al. "T-SGX: Eradicating controlled-channel attacks against enclave programs", NDSS 2017.

Shinde et al. "Preventing page faults from telling your secrets", AsiaCCS 2016.

Naive solutions: Hiding enclave page faults



... But stealthy attacker can learn page visits without triggering faults!

Documented side-effects of address translation

4.8 ACCESSED AND DIRTY FLAGS

For any paging-structure entry that is used during linear-address translation, bit 5 is the **accessed** flag.² For paging-structure entries that map a page (as opposed to referencing another paging structure), bit 6 is the **dirty** flag. These flags are provided for use by memory-management software to manage the transfer of pages and paging structures into and out of physical memory.

Whenever the processor uses a paging-structure entry as part of linear-address translation, it sets the accessed flag in that entry (if it is not already set).


Whenever there is a write to a linear address, the processor sets the dirty flag (if it is not already set) in the paging-structure entry that identifies the final physical address for the linear address (either a PTE or a paging-structure entry in which the PS flag is 1).

Telling your secrets without page faults

1. Attack vector: PTE status flags:

- A(ccessed) bit
- D(irty) bit

~> Also updated in enclave mode!



Telling your secrets without page faults

1. **Attack vector:** PTE status flags:


- A(ccessed) bit
- D(irty) bit

→ Also updated in enclave mode!

2. **Attack vector:** Unprotected **page table** **memory:**

- Cached as regular data
- Accessed during address translation

→ Flush+Reload cache timing attack!



Attacking Libcrypt EdDSA (simplified)

```
1  if (mpi_is_secure (scalar)) {  
2      /* If SCALAR is in secure memory we assume that it is the  
3         secret key we use constant time operation. */  
4      point_init (&tmppnt);  
5  
6      for (j=nbits-1; j >= 0; j--) {  
7          _gcry_mpi_ec_dup_point (result, result, ctx);  
8          _gcry_mpi_ec_add_points (&tmppnt, result, point, ctx);  
9          point_swap_cond (result, &tmppnt, mpi_test_bit (scalar, j), ctx);  
10     }  
11     point_free (&tmppnt);  
12 } else {  
13     for (j=nbits-1; j >= 0; j--) {  
14         _gcry_mpi_ec_dup_point (result, result, ctx);  
15         if (mpi_test_bit (scalar, j))  
16             _gcry_mpi_ec_add_points (result, result, point, ctx);  
17     }  
18 }
```

Memory layout

...	
gcry_free	0x0F000
...	
mpi_add	0xC0000
mpi_test_bit	0xC1000
...	
mpi_ec_add_p	0xC9000
mpi_ec_mul_p	0xCA000
...	

**22 Code pages
per iteration**

Attacking Libcrypt EdDSA (simplified)

```
1  if (mpi_is_secure (scalar)) {
2      /* If SCALAR is in secure memory we assume that it is the
3       secret key we use constant time operation. */
4      point_init (&tmppnt);
5
6      for (j=nbits-1; j >= 0; j--) {
7          _gcry_mpi_ec_dup_point (result, result, ctx);
8          _gcry_mpi_ec_add_points (&tmppnt, result, point, ctx);
9          point_swap_cond (result, &tmppnt, mpi_test_bit (scalar, j), ctx);
10     }
11     point_free (&tmppnt);
12 } else {
13     for (j=nbits-1; j >= 0; j--) {
14         _gcry_mpi_ec_dup_point (result, result, ctx);
15         if (mpi_test_bit (scalar, j))
16             _gcry_mpi_ec_add_points (result, result, point, ctx);
17     }
18 }
```

**Monitor
trigger page**



Memory layout

...	
gcry_free	0x0F000
...	
mpi_add	0xC0000
mpi_test_bit	0xC1000
...	
mpi_ec_add_p	0xC9000
mpi_ec_mul_p	0xCA000
...	

Attacking Libgcrypt EdDSA (simplified)

```
1  if (mpi_is_secure (scalar)) {
2      /* If SCALAR is in secure memory we assume that it is the
3       secret key we use constant time operation. */
4      point_init (&tmppnt);
5
6      for (j=nbits-1; j >= 0; j--) {
7          _gcry_mpi_ec_dup_point (result, result, ctx);
8          _gcry_mpi_ec_add_points (&tmppnt, result, point, ctx);
9          point_swap_cond (result, &tmppnt, mpi_test_bit (scalar, j), ctx);
10     }
11     point_free (&tmppnt);
12 } else {
13     for (j=nbits-1; j >= 0; j--) {
14         _gcry_mpi_ec_dup_point (result, result, ctx);
15         if (mpi_test_bit (scalar, j))
16             _gcry_mpi_ec_add_points (result, result, point, ctx);
17     }
18 }
```

Memory layout

...	
gcry_free	0x0F000
...	
mpi_add	0xC0000
mpi_test_bit	0xC1000
...	
mpi_ec_add_p	0xC9000
mpi_ec_mul_p	0xCA000
...	



INTERRUPT

Attacking Libgcrypt EdDSA (simplified)

```
1  if (mpi_is_secure (scalar)) {
2      /* If SCALAR is in secure memory we assume that it is the
3       secret key we use constant time operation. */
4      point_init (&tmppnt);
5
6      for (j=nbits-1; j >= 0; j--) {
7          _gcry_mpi_ec_dup_point (result, result, ctx);
8          _gcry_mpi_ec_add_points (&tmppnt, result, point, ctx);
9          point_swap_cond (result, &tmppnt, mpi_test_bit (scalar, j), ctx);
10     }
11     point_free (&tmppnt);
12 } else {
13     for (j=nbits-1; j >= 0; j--) {
14         _gcry_mpi_ec_dup_point (result, result, ctx);
15         if (mpi_test_bit (scalar, j))
16             _gcry_mpi_ec_add_points (result, result, point, ctx);
17     }
18 }
```

Record page set
0011

ACCESSED ?



ACCESSED ?

Memory layout

...	
gcry_free	0x0F000
...	
mpi_add	0xC0000
mpi_test_bit	0xC1000
...	
mpi_ec_add_p	0xC9000
mpi_ec_mul_p	0xCA000
...	

Attacking Libcrypt EdDSA (simplified)

```
1  if (mpi_is_secure (scalar)) {
2      /* If SCALAR is in secure memory we assume that it is the
3         secret key we use constant time operation. */
4      point_init (&tmppnt);
5
6      for (j=nbits-1; j >= 0; j--) {
7          _gcry_mpi_ec_dup_point (result, result, ctx);
8          _gcry_mpi_ec_add_points (&tmppnt, result, point, ctx);
9          point_swap_cond (result, &tmppnt, mpi_test_bit (scalar, j), ctx);
10     }
11     point_free (&tmppnt);
12 } else {
13     for (j=nbits-1; j >= 0; j--) {
14         _gcry_mpi_ec_dup_point (result, result, ctx);
15         if (mpi_test_bit (scalar, j))
16             _gcry_mpi_ec_add_points (result, result, point, ctx);
17     }
18 }
```

Full 512-bit key recovery, single run

Memory layout

...	
gcry_free	0x0F000
...	
mpi_add	0xC0000
mpi_test_bit	0xC1000
...	
mpi_ec_add_p	0xC9000
mpi_ec_mul_p	0xCA000
...	



RESUME

Side-channel analysis: From metadata patterns to secrets

Handwritten notes and annotations on a memory dump:

- Left margin:** "more pages accessed..." with a red triangle and arrow pointing to the memory dump.
- Top right:** "~p. 27"
- Right side:** "GPG ERR" (circled in red) and "ONE <? ZERO" (circled in blue).
- Bottom right:** "7B87" and "7BA0" (handwritten).
- Bottom left:** "MONITOR" (handwritten) with an arrow pointing to the memory dump.
- Bottom center:** "IRQ" (handwritten) with an arrow pointing to the memory dump.


Memory dump content (hex addresses and assembly instructions):

```
0x7ffffb9e000 28 <_gcry_mpi_free_limb_space>
0x7ffffb03000 7 <_gcry_free>
0x7ffff7aff000 1 <_errno_location@plt>
0x7ffff774e000 3 <_GI__errno_location>
0x7ffffb03000 6 <_gcry_free+19>
0x7ffffb08000 17 <_gcry_private_free>
0x7ffff7aff000 1 <free@plt>
0x7ffff77b1000 20 <_GI__libc_free>
0x7ffff77ad000 78 <_int_free>
0x7ffff77b1000 6 <_GI__libc_free+76>
0x7ffffb03000 8 <_gcry_free+77>
0x7ffff7aff000 1 <gpg_err_set_errno@plt>
0x7ffff7524000 1 <gpg_err_set_errno>
0x7ffff751b000 4 <_gpg_err_set_errno>
0x7ffff774e000 3 <_GI__errno_location>
0x7ffff751b000 3 <_gpg_err_set_errno+8>
0x7ffffb98000 26 <_gcry_mpi_tdiv_qr+500>
0x7ffffb00000 3 <_gcry_mpi_ec_mul_point+1081>
0x7ffffb97000 11 <_gcry_mpi_test_bit>
0x7ffffb00000 6 <_gcry_mpi_ec_mul_point+1092>
0x7ffffb9e000 176 <point_set>
0x7ffffb00000 2 <_gcry_mpi_ec_mul_point+1111>
```

Scientific Understanding Driven by Attacker-Defender Race . . .



Scientific Understanding Driven by Attacker-Defender Race . . .





1. Privileged Side-Channel Attacks

Idea #3: Spatial vs. Temporal Resolution?

Intel's note on side-channel attacks (revisited)

Protection from Side-Channel Attacks

Intel® SGX does not provide explicit protection from side-channel attacks. It is the enclave developer's responsibility to address side-channel attack concerns.

In general, enclave operations that require an OCall, such as thread synchronization, I/O, etc., are exposed to the untrusted domain. If using an OCall would allow an attacker to gain insight into enclave secrets, then there would be a security concern. This scenario would be classified as a side-channel attack, and it would be up to the ISV to design the enclave in a way that prevents the leaking of side-channel information.

An attacker with access to the platform can see what pages are being executed or accessed. This side-channel vulnerability can be mitigated by aligning specific code and data blocks to exist entirely within a single page.

More important, the application enclave should use an appropriate crypto implementation that is side channel attack resistant inside the enclave if side-channel attacks are a concern.



Temporal resolution limitations for the page fault oracle

```
1 size_t strlen (char *str)
2 {
3     char *s;
4
5     for (s = str; *s; ++s);
6     return (s - str);
7 }
```

```
1     mov    %rdi,%rax
2 1:  cmpb   $0x0,(%rax)
3     je     2f
4     inc    %rax
5     jmp    1b
6 2:  sub    %rdi,%rax
7     retq
```


⇒ tight loop: 4 instructions, single memory operand, single code + data page

Counting strlen loop iterations?



Note: Page-fault attacks cannot make progress for 1 code + data page

Temporal resolution limitations for the page fault oracle




Counting strlen loop iterations?



Progress requires **both pages present** (non-faulting) ↔ page fault oracle


Building the `strlen()` side-channel oracle with execution timing?



Building the `strlen()` side-channel oracle with execution timing?



Too noisy: modern x86 processors are lightning fast...



Challenge: Side-channel Sampling Rate



**Slow
shutter speed**




**Medium
shutter speed**




**Fast
shutter speed**

SGX-Step: Executing Enclaves one Instruction at a Time



SGX-Step: Executing Enclaves one Instruction at a Time



SGX-Step demo: Building a memcmp() Password Oracle

```
[idt.c] DTR.base=0xffffffff0000000000/size=4095 (256 entries)
[idt.c] established user space IDT mapping at 0x7f7ff8e9a000
[idt.c] installed asm IRQ handler at 10:0x56312d19b000
[idt.c] IDT[ 45] @0x7f7ff8e9a2d0 = 0x56312d19b000 (seg sel 0x10); p=1; dpl=3; type=14; ist=0
[file.c] reading buffer from '/dev/cpu/1/msr' (size=8)
[apic.c] established local memory mapping for APIC_BASE=0xfe00000 at 0x7f7ff8e99000
[apic.c] APIC_ID=2000000; LVTT=400ec; TDCR=0
[apic.c] APIC timer one-shot mode with division 2 (lvtt=2d/tdcr=0)
```

```
-----
[main.c] recovering password length
-----
```

```
[attacker] steps=15; guess='*****'
[attacker] found pwd len = 6
```

```
-----
[main.c] recovering password bytes
-----
```

```
[attacker] steps=35; guess='SECRET' --> SUCCESS
```


```
[apic.c] Restored APIC_LVTT=400ec/TDCR=0)
[file.c] writing buffer to '/dev/cpu/1/msr' (size=8)
[main.c] all done; counted 2260/2183 IRQs (AEP/IDT)
jo@breuer:~/sgx-step-demo$ █
```

SGX-Step: Enabling a New Line of High-Resolution Attacks

Yr	Venue	Paper	Step	Use Case	Drv
'15	S&P	Ctrl channel	~ Page	Probe (page fault)	✓
'16	ESORICS	AsyncShock	~ Page	Exploit (mem safety)	–
'17	CHES	CacheZoom	✗ >1	Probe (L1 cache)	✓
'17	ATC	Hahnel et al.	✗ 0 - >1	Probe (L1 cache)	✓
'17	USENIX	BranchShadow	✗ 5 - 50	Probe (BPU)	✗
'17	USENIX	Stealthy PTE	~ Page	Probe (page table)	✓
'17	USENIX	DarkROP	~ Page	Exploit (mem safety)	✓
'17	SysTEX	SGX-Step	✓ 0 - 1	Framework	✓
'18	ESSoS	Off-limits	✓ 0 - 1	Probe (segmentation)	✓
'18	AsiaCCS	Single-trace RSA	~ Page	Probe (page fault)	✓
'18	USENIX	Foreshadow	✓ 0 - 1	Probe (transient exec)	✓
'18	EuroS&P	SgxPectre	~ Page	Exploit (transient)	✓
'18	CHES	CacheQuote	✗ >1	Probe (L1 cache)	✓
'18	ICCD	SGXlinger	✗ >1	Probe (IRQ latency)	✗
'18	CCS	Nemesis	✓ 1	Probe (IRQ latency)	✓
'19	USENIX	Spoiler	✓ 1	Probe (IRQ latency)	✓
'19	CCS	ZombieLoad	✓ 0 - 1	Probe (transient exec)	✓
'19	CCS	Fallout	–	Probe (transient exec)	✓
'19	CCS	Tale of 2 worlds	✓ 1	Exploit (mem safety)	✓
'19	ISCA	MicroScope	~ 0 - Page	Framework	✗
'20	CHES	Bluthunder	✓ 1	Probe (BPU)	✓
'20	USENIX	Big troubles	~ Page	Probe (page fault)	✓
'20	S&P	Plundervolt	–	Exploit (undervolt)	✓
'20	CHES	Viral primitive	✓ 1	Probe (IRQ count)	✓
'20	USENIX	CopyCat	✓ 1	Probe (IRQ count)	✓
'20	S&P	LVI	✓ 1	Exploit (transient)	✓

Yr	Venue	Paper	Step	Use Case	Drv
'20	CHES	A to Z	~ Page	Probe (page fault)	✓
'20	CCS	Déjà Vu NSS	~ Page	Probe (page fault)	✓
'20	MICRO	PTHammer	–	Probe (page walk)	✓
'21	USENIX	Frontal	✓ 1	Probe (IRQ latency)	✓
'21	S&P	CrossTalk	✓ 1	Probe (transient exec)	✓
'21	CHES	Online template	✓ 1	Probe (IRQ count)	✓
'21	NDSS	SpeechMiner	–	Framework	✓
'21	S&P	Platypus	✓ 0 - 1	Probe (voltage)	✓
'21	DIMVA	Aion	✓ 1	Probe (cache)	✓
'21	CCS	SmashEx	✓ 1	Exploit (mem safety)	✓
'21	CCS	Util::Lookup	✓ 1	Probe (L3 cache)	✓
'22	USENIX	Rapid prototyping	✓ 1	Framework	✓
'22	CT-RSA	Kalyana expansion	✓ 1	Probe (L3 cache)	✓
'22	SEED	Enclyzer	–	Framework	✓
'22	NordSec	Self-monitoring	~ Page	Defense (detect)	✓
'22	AutoSec	Robotic vehicles	✓ 1 - >1	Exploit (timestamp)	✓
'22	ACSAC	MoLE	✓ 1	Defense (randomize)	✓
'22	USENIX	AEPIC	✓ 1	Probe (I/O device)	✓
'22	arXiv	Confidential code	✓ 1	Probe (IRQ latency)	✓
'23	ComSec	FaultMorse	~ Page	Probe (page fault)	✓
'23	CHES	HQC timing	✓ 1	Probe (L3 cache)	✓
'23	ISCA	Belong to us	✓ 1	Probe (BPU)	✓
'23	USENIX	BunnyHop	✓ 1	Probe (BPU)	✓
'23	USENIX	DownFall	✓ 0 - 1	Probe (transient exec)	✓
'23	USENIX	AEX-Notify	✓ 1	Defense (prefetch)	✓

A Versatile Open-Source Attack Toolkit







1. Privileged Side-Channel Attacks

Idea #4: Temporal Hardening?

Root-causing SGX-Step: Aiming the timer interrupt



Root-causing SGX-Step: Microcode assists to the rescue!

PTE A-bit	Mean (cycles)	Stddev (cycles)
A=1	27	30
A=0	666	55



3. Assisted PT walk



1. Clear PTE A-bit



2. TLB flush




page walk (\$RIP)

exec


Arm timer

ERESUME

NOP₁






AEX-Notify solution overview



AEX-Notify solution overview

We implemented a fast, constant-time decoder (CTD)



CHAPTER 8

ASYNCHRONOUS ENCLAVE EXIT NOTIFY AND THE EDECCSSA USER LEAF FUNCTION

8.1 INTRODUCTION

Asynchronous Enclave Exit Notify (AEX-Notify) is an extension to Intel® SGX that allows Intel SGX enclaves to be notified after an asynchronous enclave exit (AEX) has occurred. EDECCSSA is a new Intel SGX user leaf function (ENCLU[EDECCSSA]) that can facilitate AEX notification handling, as well as software exception handling. This chapter provides information about changes to the Intel SGX architecture that support AEX-Notify and ENCLU[EDECCSSA].

The following list summarizes the changes. Details are provided in Section 8.3.

- SECS.ATTRIBUTES.AEXNOTIFY: This bit enables AEX notifications.
- TCS.FLAGS.AEXNOTIFY: This bit enables AEX notifications.
- SSA.GPRSGX.AEXNOTIFY: Enclave-writable byte that allows enclave software to dynamically enable/disable AEX notifications.

An AEX notification is delivered by ENCLU[ERESUME] when the following conditions are met:



*SGX-Step led to **new x86 processor instructions!***

→ shipped in millions of devices ≥ 4th Gen Xeon CPU

Intel AEX Notify Support Prepped For Linux To Help Enhance SGX Enclave Security

Written by [Michael Larabel](#) in [Intel](#) on 6 November 2022 at 06:01 AM EST. [5 Comments](#)



Future Intel CPUs and some existing processors via a microcode update will support a new feature called the Asynchronous EXit (AEX) notification mechanism to help with Software Guard Extensions (SGX) enclave security. Patches for the Linux kernel are pending for implementing this Intel AEX Notify support with capable processors.

Intel's Asynchronous EXit (AEX) notification mechanism lets SGX enclaves run a handler after an AEX event. Those handlers can be used for things like mitigating SGX-Step as an attack framework for precise enclave execution control.



Code **1** in [intel/linux-sgx](#)

Filter

 sdk/trts/linux/trts_mitigation.S

```
48  * Description:
49  *   The file provides mitigations for SGX-Step
50  */
71  * Function:
   constant_time_apply_sgxstep_mitigation_and_continue_execution
72  *   Mitigate SGX-Step and return to the point at which the
   most recent
73  *   interrupt/exception occurred.
```



*SGX-Step led to **changes** in major OSs and enclave SDKs*




1. Privileged Side-Channel Attacks

Idea #5: Spatial Hardening?

There's a Catch...

Finally note that our proposed mitigation does not protect against interrupting enclaves and observing application code and data page accesses at a coarse-grained 4 KiB spatial resolution. In contrast to the fine-grained, instruction-granular interrupt-driven attacks we consider in this work, such controlled-channel attacks have received ample attention [18, 47, 56, 59] from the research community.

Why Mitigating Single-Stepping is Not Enough




Original (left), Xu et al. (middle), our attack with AEX-Notify single-stepping defense (right)


□ Xu et al.: “Controlled-channel attacks: Deterministic side channels for untrusted operating systems”, Oakland 2015.

□ Constable et al.: “AEX-Notify: Thwarting Precise Single-Stepping Attacks through Interrupt Awareness for Intel SGX Enclaves”, USENIX Security 2023.


Libjpeg: AEX-Notify's Temporal Reduction in Practice




Libjpeg: AEX-Notify's Temporal Reduction in Practice



Libjpeg: AEX-Notify's Temporal Reduction in Practice




Idea: TLB as a “Filter” to Hide Page Accesses




□ Vanoverloop et al.: “TLBlur: Compiler-Assisted Automated Hardening against Controlled Channels on Off-the-Shelf Intel SGX Platforms”,
USENIX Security 2025.


TLBlur: Self-Monitoring and Restoring Enclave Page Accesses




Instrumentation to Self-Monitor Page Accesses at Runtime




Leakage Reduction in Practice: libjpeg with Single Stepping




Leakage Reduction in Practice: libjpeg with Page Faults




Leakage Reduction in Practice: libjpeg with TLBlur ($N = 10$)



Leakage Reduction in Practice: libjpeg with TLBlur ($N = 20$)



Leakage Reduction in Practice: libjpeg with TLBlur ($N = 30$)






2. Transient-Execution Attacks

Revisited: Intel's note on side-channel attacks (2017)



"In general, these research papers do not demonstrate anything new or unexpected about the Intel SGX architecture. Preventing side channel attacks is a matter for the enclave developer. Intel makes this clear in the security objectives for Intel SGX."

<https://www.intel.com/content/www/us/en/developer/articles/technical/intel-sgx-and-side-channels.html>

Recap: Privileged side-channel attacks



Recap: Transient-execution attacks




A close-up of Morpheus from the movie The Matrix, wearing his signature black sunglasses. The reflection in the lenses shows three figures in a room, likely the iconic 'The Blue Pill or the Red Pill' scene. The background is a blurred, dimly lit interior.


WHAT IF I TOLD YOU

YOU CAN CHANGE RULES MID-GAME


Abusing out-of-order and speculative execution



Abusing out-of-order and speculative execution



Abusing out-of-order and speculative execution




Transient-execution attacks: Welcome to the world of fun!



The transient-execution zoo

<https://transient.fail>






2. Transient-Execution Attacks

Confused-deputy code gadgets?


Spectre v1: Speculative buffer over-read



```
if (idx < LEN)
{
    s = buffer[idx];
    t = lookup[s];
    ...
}
```

- Programmer *intention*: no out-of-bounds accesses


Spectre v1: Speculative buffer over-read



```
if (idx < LEN)
{
    s = buffer[idx];
    t = lookup[s];
    ...
}
```

- Programmer *intention*: no out-of-bounds accesses
- **Mistrain gadget** to **speculatively** “ahead of time” execute with $idx \geq LEN$ in the transient world


Spectre v1: Speculative buffer over-read



```
if (idx < LEN)
{
    s = buffer[idx];
    t = lookup[s];
    ...
}
```

- Programmer *intention*: no out-of-bounds accesses
- **Mistrain gadget** to **speculatively** “ahead of time” execute with $idx \geq LEN$ in the transient world
- **Side channels** may leave traces after roll-back!

Spectre v1: Speculative buffer over-read



```
if (idx < LEN)
{
    asm("lfence\n\t");
    s = buffer[idx];
    t = lookup[s];
    ...
}
```

- Programmer *intention*: no out-of-bounds accesses
- **Mistrain gadget** to **speculatively** “ahead of time” execute with $idx \geq LEN$ in the transient world
- **Side channels** may leave traces after roll-back!
- Insert explicit **speculation barriers** to tell the CPU to halt the transient world...

Spectre take-away

- CPU **transiently** executes wrong code paths
- **Confused-deputy gadgets** encode secrets via side channels





2. Transient-Execution Attacks


Transient access-control bypass?



insideTM



insideTM



insideTM

Meltdown: Transiently encoding unauthorized memory



Unauthorized access


Listing 1: x86 assembly

```
1 meltdown:
2   // %rdi: oracle
3   // %rsi: secret_ptr
4
5   movb (%rsi), %al
6   shl $0xc, %rax
7   movq (%rdi, %rax), %rdi
8   retq
```

Listing 2: C code.

```
1 void meltdown(
2     uint8_t *oracle,
3     uint8_t *secret_ptr)
4 {
5     uint8_t v = *secret_ptr;
6     v = v * 0x1000;
7     uint64_t o = oracle[v];
8 }
```

Meltdown: Transiently encoding unauthorized memory



Unauthorized access



Transient out-of-order window


Listing 1: x86 assembly.

```
1 meltdown:
2   // %rdi: oracle
3   // %rsi: secret_ptr
4
5   movb (%rsi), %al
6   shl $0xc, %rax
7   movq (%rdi, %rax), %rdi
8   retq
```

Listing 2: C code.


```
1 void meltdown(
2     uint8_t *oracle,
3     uint8_t *secret_ptr)
4 {
5     uint8_t v = *secret_ptr;
6     v = v * 0x1000;
7     uint64_t o = oracle[v];
8 }
```

oracle array



secret idx

Meltdown: Transiently encoding unauthorized memory



Unauthorized access



Transient out-of-order window



Exception

(discard architectural state)


Listing 1: x86 assembly.

```
1 meltdown:
2   // %rdi: oracle
3   // %rsi: secret_ptr
4
5   movb (%rsi), %al
6   shl $0xc, %rax
7   movq (%rdi, %rax), %rdi
8   retq
```

Listing 2: C code.

```
1 void meltdown(
2     uint8_t *oracle,
3     uint8_t *secret_ptr)
4 {
5     uint8_t v = *secret_ptr;
6     v = v * 0x1000;
7     uint64_t o = oracle[v];
8 }
```

Meltdown: Transiently encoding unauthorized memory



Unauthorized access



Transient out-of-order window



Exception handler

Listing 1: x86 assembly.

```
1 meltdown:
2   // %rdi: oracle
3   // %rsi: secret_ptr
4
5   movb (%rsi), %al
6   shl $0xc, %rax
7   movq (%rdi, %rax), %rdi
8   retq
```


Listing 2: C code.

```
1 void meltdown(
2     uint8_t *oracle,
3     uint8_t *secret_ptr)
4 {
5     uint8_t v = *secret_ptr;
6     v = v * 0x1000;
7     uint64_t o = oracle[v];
8 }
```

oracle array



MDS variants: Flushing additional microarchitectural buffers



Meltdown take-away

- **Faulting** loads transiently forward data from various microarchitectural buffers
- **Hardware fixes** for recent CPUs





Conclusions and Outlook



Takeaways

- ⇒ **Trusted execution** environments (Intel SGX) $\neq$ perfect!
- ⇒ Privileged adversaries: Subtle **side channels** can go a long way...
- ⇒ Scientific understanding driven by **attacker-defender race**



Thank you! Questions?